



# Unique Features of the AS720

## **Tank Capacity**

750 gallons

#### **Transmission**

JCB transmission Power Shift, 4-speed

# Engine

Tier 3 160 hp Cummins engine

# **Top Road Speed**

28 MPH

## Weight

19,200 lbs (approx. dry weight)

# **Crop Clearance**

42" with JCB planetary final drives 50" clearance with 18" drop box all-gear final drives (optional)



# **COMMON FEATURES FOR ALL APACHE MODELS**

ENGINE & DRIVE TRAIN	FUEL CAPACITY	100 gallons
CHASSIS, SUSPENSION & TIRES	SUSPENSION	Patented independent hydraulic
	BRAKES	Fully enclosed, self-adjusting, internal wet disc brakes
	FRONT TIRES	380/80R38 (narrow and semi-float options available)
	REAR TIRES	380/90R46 (narrow, semi-float, and full-float options available)
	TRANSPORT WIDTH AND HEIGHT	144" maximum
් 	OVERALL LENGTH	290" maximum
SPRAY OPTIONS	BOOMS	Ст си <b>этом воом</b> Straight 90' or 100'; or 60'/90' Straight 120' or 132'
	PRODUCT PUMP	HYPRO,® Hydraulically-driven centrifugal product pump
	RINSE TANK	100 gallons
CAB	ET CUSTOM PRESSURIZED	State-of-the-art cab interior and console

PRECISION APPLICATION EQUIPMENT AVAILABLE FACTORY-INSTALLED ON ALL NEW APACHES BY RAVEN AND STrimble

All Model Year 2016 Apache sprayers are available with optional ISOBUS-ready wiring in lieu of factory-installed field computers. Refer to your specific precision agriculture product documentation for compatibility information. Equipment Technologies factory installs all field computers using CAN bus wiring and protocols.

